

FEATURE

Model PT-100 prints measuring and weighting data of indicator. It is a high speed, ultra-small size, and thermal transfer type printer for industry.

- Ultra-small size panel type
- Easy to change the paper (Clamshell structure)
- Silent and rapid printing speed (50mm/sec)
- convenient head cleaning

SPECIFICATION

Header	203 dpi (8.0 dots/mm) 2" (48mm/384 dots) / 40 column
Parallel port	RS232C (300bps ~ 12kbps)
Paper	Thermal transfer label paper
Paper size	57mm wide, roll
Power	AC 90 ~ 240V 50/60Hz
Operating temperature	0 ~ 40 °C
Operating humidity	20 ~ 80%
Print head duration	50km
Weight	About 800g

► Protocol

- Data bit : 8 bit
- Parity : no parity
- Stop bit : 1 bit

► Data format

<EX> IDNO : 00021, DATA : +0622.5

Byte	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23
Data	N	0	:	0	0	0	2	1	SPACE	M	E	A	S	:	*	0	6	2	2	.	5	CR	LF
ASC II	4E	4F	3A	30	30	30	32	31	20	4D	45	41	53	3A	2B	30	36	32	32	2E	35	0D	0A



DIMENSION

